



**A CASE HISTORY**

# Anchors and Foundations for Telecom Industry

Site Owner: American Tower Corporation

Tower Supplier: Allied Tower  
Foundation Contractor: Lomas Construction  
San Antonio, TX

Location: Gibson, LA

Tower Type : Guyed (4 Levels)  
 Tower Height : 330'-0  
 Center (Base) Reactions:  
   Maximum Compression                   331.4 kips\*  
   Maximum Groundline Shear           6.1 kips  
   \*Plus weight of concrete pile cap of 40.0 kips  
 Design Load/Guy wire:                   34.0 kips  
 Soil Profile:  
   0 - 80'           Soft clay  
   80' plus        Firm clay  
 Center Piles:  
   16 Type HS with 85'-0 of plain extension  
   Ultimate Capacity (UCt) = UCb + UCf  
   UCt = 48.0 + 0.0 = 48.0 kips  
 Guy Anchors:  
   Two Type SS5 anchors per guy wire connected  
   to an 18" Adjust-A-Grip® Deadend Grip

Installation Equipment:  
 John Deere 410D Heavy-lift backhoe equipped  
 with a 12,500. ft-lb drive motor with an internal  
 torque-monitoring device  
 Posi-Track equipped with a 15,000. ft-lb drive  
 motor with an internal torque-monitoring device



• Individual guy wires, each to two anchors



[www.abchance.com](http://www.abchance.com)

A.B. Chance, a Division of Hubbell Power Systems, Inc.  
 210 N. Allen St.  
 Centralia, MO 65240  
 Phone: 573-682-8414  
 Fax: 573-682-8660

©2006 Hubbell  
 Printed in USA  
 RGS

ISO 9001:2000



Certificate No. 001136

Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.

Bulletin 02-0002  
Rev. 3/06